

Varilla corrugada

No.	DIAMETRO NOMINAL		AREA NOMINAL		PESO UNITARIO		PERIMETRO		NUMERO APROXIMADO DE VARILLAS DE 12 mts x ton
	mm	Pulg	mm ²	Pulg ²	kg/m	Lb/pie	mm	Pulg	
2.5	7.9	5/16	49	0.08	0.384	0.261	24.8	0.982	217
3	9.5	3/8	71	0.11	0.557	0.376	29.8	1.178	150
4	12.7	1/2	127	0.20	0.996	0.668	39.9	1.571	84
5	15.9	5/8	199	0.31	1.560	1.040	50.0	1.963	53
6	19.1	3/4	287	0.44	2.250	1.502	60.0	2.356	37
7	22.2	7/8	387	0.60	3.034	2.044	69.7	2.749	27
8	25.4	1"	507	0.79	3.975	2.670	79.8	3.142	21
9	28.6	1-1/8	642	0.99	5.033	3.381	89.8	3.534	17
10	31.8	1-1/4	794	1.23	6.225	4.172	99.9	3.927	13
11	34.9	1-3/8	957	1.48	7.503	5.049	109.6	4.320	11
12	38.1	1-1/2	1140	1.77	8.938	6.008	119.7	4.712	9

VARILLA CORRUGADA GRADO 42
 LIMITE DE FLUENCIA MINIMA 4200 kg/cm²
 RESISTENCIA A LA TENCION MINIMA 5300 kg/cm²